OIL FILLING VACUUM DEGASSING SYSTEM

MOBILE, 30 LITRE CAPACITY, GLASS VACUUM CHAMBER, CENTRAL CONTROL PANEL

The Oil Filling/Vacuum <u>Degassing System</u> consists of a mobile, trolley mounted, glass oil reservoir with aluminium base and top plates, fluid and vacuum pumps and a control panel with vacuum, fluid and temperature instrumentation.

PRINCIPLE OF OPERATION

During the degassing cycle, the fluid pump continually circulates oil through an in-line filter, heater block and spreader plate, back into the reservoir

Throughout this cycle the chamber is evacuated using the onboard vacuum pump

Pressure is monitored via gauges mounted on the control panel

During the tool fill cycle, the operator evacuates the tool, then diverts the flow of oil to fill the tool

An indicator on the control panel, when illuminated, warns the operator of the need to replace the filter

The system is bunded with a built in tray providing 110% oil capture capacity

The system is mounted on a 300kg capacity trolley with tough impact-resistant 1-piece plastic shelves, polypropylene castor housing, cushion rubber wheels for smooth movement and a handle

TECHNICAL SPECIFICATION

Borosilicate 3.3 glass
30 litres
<1 x 10 ⁻¹ mbar
e 1 litre/min
230V, 50Hz, 1 ph, 3 KW
600 x 1750 x 1020 mm
706 x 300 mm
180 Kg
< 80 dB
Down to 1 micron
Ethernet - Modbus TCP
110% oil capture capability
Ambient to +60°C
Ambient to +60°C
Yes
Yes

* For guideline purposes only - subject to change

MechaTech Systems Ltd, Unit 9 Brunel Way, Thornbury Industrial Estate, Thornbury, Bristol, UK. BS35 3UR Registered in England and Wales No. 06469333 WWW.Mechatechsystems.co.uk





 $\ensuremath{\textcircled{\text{C}}}$ MechaTech Systems 2025 - All rights reserved



enquiries@mechatechsystems.co.uk +44 (0) 1454 414723